


## **SLING SHIELD™** Sling Protection

The number one cause of synthetic sling failure is cutting. **Sling Shield Edge Protectors** prevent synthetic slings from being cut by load edges. Low weight, high strength extruded aluminum body provides a full 1" radius to protect your slings from even the sharpest of load edges.

Stop replacing your synthetic slings and wear pads due to cutting.





## Features:

- Aluminum bar with 1" radius supports basket or choker sling tensions of up to 25,000 lbs. per inch of sling width
- Polycarbonate end restraints help keep slings on bar when lifting at angles
- Magnet keeps **Sling Shield** in place on steel loads while rigging the lift
- Velcro<sup>®</sup> straps help keep sling in position prior to lift

## Benefits:

- Improves Safety Eliminates dropped loads caused by load edges cutting the sling
- Saves Time Magnet and Velcro<sup>®</sup> straps greatly reduce rigging time
- Saves Money No cut slings or wear pads means fewer replacement purchases




Lift-All	SS Inside	SS Overall	SS Weight	Widest	Largest Appropriate Tuflex Size		Largest Appropriate KeyFlex Size	
Part #	Width (In.)	Length (In.)	(Lbs.)	Web Sling (In.)	Single Leg	Double Leg	Single Leg	Double Leg
SS1-4	4.50	7.50	2.7	4	EN360	EN120	KEN80K	KEN15K
SS1-6	6.75	10.00	3.2	6	EN1000	EN240	KEN100K	KEN40K
SS1-12	12.75	16.00	4.8	12	EN1000	EN1000	KEN100K	KEN100K

## LOAD RATINGS

The load rating of *Sling Shields* is **25,000 lbs**. of sling tension per inch of sling width using a basket or choker hitch. This rating is reduced when lifting at side pull angles of less than 70°. Do not exceed listed sling tensions. Prevent *Sling Shield* from sliding when using at an angle. Do not use at side pull angles less than 45°. See Safety Bulletin for more detailed information.

Side Pull Angle	Basket/Choker Rating (Lbs.)*				
65°	17,500				
60°	15,000				
55°	13,000				
50°	11,000				
45°	8,000				





800-909-1964 www.lift-all.com

<sup>\*</sup> Ultimate rating regardless of width. Lifting in a vertical hitch reduces these ratings by half.