

“easy” Torque

- Audible Click At Torque
- Replaceable Blades
- +/- 10% Repeatability
- Improve Productivity
- Reduces Waste
- Controls Costs
- Save Time!



Each tool factory preset

Torque accuracy of +/- 10% to 5000 cycles

Economical Torque Control for tooling assembly and repair

Uses 285 Series interchangeable blades on page 4

Reverse torque is 50% greater for easy removal using same tool

Wiha Easy Torque Handles



[SHOP](#)

292 Easy Torque Screwdriver Handle

Easy Torque value pre-set. Release accuracy +/- 10%. SoftFinish cushion grip handle for good power transfer.

Item No.	Pre-Sets		mm	Inch	lbs.	pkg.
	Inch/lbs.	Nm				
29205	4.4	0.5	294	5.4	.20	1
29206	5.3	0.6	294	5.4	.20	1
29209	8.0	0.9	294	5.4	.20	1
29211	9.7	1.1	294	5.4	.20	1
29212	10.6	1.2	294	5.4	.20	1
29214	12.4	1.4	294	5.4	.20	1
29220	17.7	2.0	294	5.4	.20	1
29225	22.1	2.5	294	5.4	.20	1
29230	26.6	3.0	294	5.4	.20	1
29238	33.6	3.8	294	5.4	.20	1
29241	35.4	4.0	294	5.4	.20	1
29245	39.8	4.5	294	5.4	.20	1
29251	44.2	5.0	294	5.4	.20	1

* No Calibration Certificates

- Handles are larger for easier Torque application
- SoftFinish Cushion Grips for improved user Comfort
- Design has been improved to add significantly to durability and overall tool life.
- Accuracy remains at +/- 10% with NO certificate of calibration.
- Three additional Torque Handles have been added
4 Nm, 4.5 Nm, 5 Nm



[SHOP](#)

292 Easy Torque Screwdriver Handle With TORX® Blades

Easy Torque value pre-set. Release accuracy +/- 10%.

Internal mechanism clicks when torque value has been attained.

Cushion grip comfortable handle for good power transfer.

Item No.	Size	Pre-Sets		lbs.	pkg.
		Inch/lbs.	Nm		
29232	T5	4.4	0.5	.24	1
29233	T6	5.3	0.6	.24	1
29234	T7	8.0	0.9	.24	1
29236	T8	10.6	1.2	.25	1
29237	T9	12.4	1.4	.25	1
29239	T10	17.7	2.0	.26	1
29242	T15	26.6	3.0	.26	1
29243	T20	35.4	4.0	.26	1
29244	T25	44.2	5.0	.28	1

* No Calibration Certificates



[SHOP](#)

292 Easy Torque Screwdriver Handle With TORXPlus® Blades

Easy Torque value pre-set. Release accuracy +/- 10%.

Internal mechanism clicks when torque value has been attained.

Cushion grip comfortable handle for good power transfer.

Item No.	Size	Pre-Sets		lbs.	pkg.
		Inch/lbs.	Nm		
29246	IP5	4.4	0.5	.24	1
29247	IP6	5.3	0.6	.24	1
29248	IP7	8.0	0.9	.24	1
29249	IP8	10.6	1.2	.25	1
29252	IP9	12.4	1.4	.25	1
29253	IP10	17.7	2.0	.26	1
29254	IP15	26.6	3.0	.26	1
29255	IP20	35.4	4.0	.26	1
29256	IP25	44.2	5.0	.28	1

* No Calibration Certificates

